

C-ARM Compatible Electromatic Remote Operated OT Table

MI 101



Technical Constraints

Top Dimension	L 1980 mm x W 533 mm
Height Adjustment	750 mm - 1050 mm
Trendelenburg/ Reverse	30° / 25°
Lateral Tilt	20° / 20°
Kidney Elevator	150 mm
Back Rest (Up/Down)	80° / 25°
Leg Rest (Up/Down)	15° / 90°
Head Rest (Up/Down)	60° / 60°
Power Supply	24V DC
Battery Backup	3 hrs. (Optional)
Patient Weight Capacity	200 kgs(440lbs)

Optional Feature



Ultra Low Height



Floor Locking by Remote

FEATURES

- Electromatic drives with noiseless, jerk less and smooth positioning.
- Table positions i.e. Height adjustment, Trendelenburg, Reverse Trendelenburg, Lateral Tilt, Back Section/Chair Position, Flex-Reflex, Zero Position are controlled by Corded Handset with graphical icons.
- Zero Position to make table neutral by simply pressing '0' positioning button.
- Remote has LED backlit with symbolic position figures to use even in darkness.
- Table top is c-arm & x-ray compatible over the entire length of the table.
- Detachable-Interchangeable head and leg sections provide further versatility.
- Non-corrosive stainless steel 304G construction including table top frames, accessories rail, base cover and column covers.
- Four easy glide, antistatic castors, two of which are swivelling, ensure mobility.
- Pedal operated braking system secures the table in its place while in use.

Standard Accessories

- Anaesthesia screen – 1 pc
- Knee crutches – 1 pair
- Lateral support – 1 pair
- Flat clamp – 7 pc
- Shoulder support – 1 pair
- Radial clamp – 1 pair
- Arm rest – 1 pair
- Mattress 50 mm – 1 set