

SPECIFICATION	Fumex - 60 Lite
Construction	ABS Housing, H.D.P.E. Tank, Handle, Tank Cover, Strainer, Hardware All S.S 304 Grade Tubing-Superior Quality Silicon (Non Collapsible)
Timer Device	Mechanical Timer 1-60 Min. ABS Box.
Run Time Counter	Not Available
Fog Reach	20 - 25 Feet
Liquid Flow rate	1 - 3 Ltrs/Hours (Adjustable)
Particle Size	Ultra Fine Sub Microns
Liquid Flow Control	Available
Nozzle Assembly	Non Rotating Vortex Design Engg. Plastic Nozzle Assembly
Area Coverage	>16000 Cuft
Solution Tank Capacity	6 Liters
Motor	22000 R.P.M. (Approx)
Noise Level	< 88 db @ 1 Meter
Air Filter	Advance Design Tripal Stage Filter
Electrical Requirement	220~230 VAC, 50/60 Hz
Fogger Weight (dry)	4-5 kg. (Approx)

Meditech Foggers are Compatible with wide range of $H_2O_2 + AgNO_3$ based chemicals

FUMEX - 60 LITE



Mechanical Timer
1 to 60 minute

📍 #487/67, Glass Street, National Market,
Peeragarhi, New Delhi - 110087, INDIA

📞 +91 11 40392484

☎ +91 9812266676

✉ marketinguk@meditech-india.com

🌐 www.mediech-india.com